

At page 1, line 30, replace 'With a view to achieving this objective, an', with --An--.

At page 2, line 7, after "pieces", replace ', which are due to' with --caused by--.

At page 2, line 8, after "heating and", delete 'to'.

At page 2, line 15, after "covers", delete 'over'.

At page 4, line 10, after "known in", replace 'itself' with --the art--.

At page 4, line 18, after "known in", replace 'itself' with --the art--.

At page 5, line 25, before "can", replace 'it, it' with --the housing, the magnet--.

At page 5, line 31, after "case", replace 'it' with --the strip--.

At page 6, line 13, after "the forces and", delete 'to'.

At page 6, line 18, after "magnet 20," insert --and--.

At page 6, line 18, after "constituted", delete 'can be'.

At page 6, line 22, after "magnet", delete 'at this stage'.

At page 6, line 27, before "strip", insert --the--.

At page 6, line 31, after "20", delete 'this time'.

At page 6, line 33, after "This", insert --material--.

At page 7, line 6, before "to the direction", replace 'perpendicularly' with --perpendicular--.

At page 7, line 9, before "also provides", delete 'itself'.

At page 7, line 10, after "deformations, ", delete 'but'.

At page 7, line 11, after "parallel," insert --but--.

At page 7, line 17, after "grooves 18", replace 'this time' with --in this embodiment--.

At page 7, line 25, after "trapezium", insert --shaped magnet--.

At page 7, line 29, after "trapezium", insert --shaped magnet--.

IN THE CLAIMS

Sub
B
1. (Amended) An alternator for a vehicle, comprising

two pole pieces having interlaced poles, and

at least one magnet, the poles [exhibiting] including grooves profiled along an axis [and] ,

the grooves accommodating the magnet between the interlaced poles of the pole pieces, the

groove profile completely preventing the magnet escaping from the grooves in a plane

perpendicular to the axis, [which comprises] and